

GBAR.EX26837 - DRY-CHEMICAL EXTINGUISHERS, HAND AND WHEELED

Dry-chemical Extinguishers, Hand and Wheeled

See General Information for Dry-chemical Extinguishers, Hand and Wheeled

VICTORY FIRE & GAS INC
1713 Lewis St
Bay City, MI 48706 USA

EX26837

Stored-pressure-type Extinguishers

Model	Nominal Agent Capacity, lb	Min Use Temp, °F	Rating	Marine Type
Ammonium phosphate				
PD2.5LB PD2.5LB-AL	2.5	-40	1-A:10-B:C	Yes
PD5LB PD5LB-AL	5.0	-40	3-A:30-B:C	Yes
PD5LB-H PD5LB-ALH	5.0	-40	3-A:40-B:C	Yes
PD10LB PD10LB-AL	10.5	-40	4-A:60-B:C	Yes
PD20LB PD20LB-AL	20.0	-40	6-A:80-B:C	Yes

Last Updated on 2017 -09-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format:
LLC"

"© 2019 UL

GBAR7.EX26837 - DRY-CHEMICAL EXTINGUISHERS, HAND AND WHEELED CERTIFIED FOR CANADA

Dry-chemical Extinguishers, Hand and Wheeled Certified for Canada

See General Information for Dry-chemical Extinguishers, Hand and Wheeled Certified for Canada

VICTORY FIRE & GAS INC
1713 Lewis St
Bay City, MI 48706 USA

EX26837

Model	Size, kg	Ratings and Classifications	Min Temp, °C
PD2.5LB, PD2.5LB-AL	1.13	1-A:10-B:C	-40
PD5LB, PD5LB-AL	2.27	3-A:30-B:C	-40
PD5LB-H, PD5LB-ALH	2.27	3-A:40-B:C	-40
PD10LB, PD10LB-AL	4.76	4-A:60-B:C	-40
PD20LB, PD20LB-AL	9.0	6-A:80-B:C	-40

Last Updated on 2017 -09-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format:
LLC"

" © 2019 UL